



High Brightness  
Diffuse Back Light

# LDL-TP-Si100x80



Operating Temperature after 30 minutes	Drawing

Mechanical Data (TYP)	
Casing Material	Aluminum + Diffuser
Storage Temperature Range	Temp 0-35°C, Humidity 20-85%
Weight	Approx. 280g

Optical Data(TYP)	R	R24	W	G	B
Illumination (number of LED)	-	180	192		
Led Color	RED		WHITE	GREEN	BLUE
Wavelength	635 nm		xy=(0.31,0.32)	525nm	470nm
Led Package	PLCC4		SMD		

Electrical Data (TYP)	R	R24	W/G/B
Operating Voltage	-	24V ± 2%	24V ± 2%
Reverse Battery Protection	-	YES	YES
Supply Ripple Voltage	-	≤ Vs ± 5%	≤ Vs ± 5%
Current Consumption	-	0.72A	0.64A
Power Consumption	-	17.28W	15.36W
Trigger Voltage	-	Continuous= 24V Pulsing 48V 0-10% Duty Cycle	Continuous= 24V Pulsing 48V 0-10% Duty Cycle
Operating after 30 minutes	Approx. 56°C		Approx. 51°C
Additional Cooling Method	Attached to large machine part		
Life span in continuous mode	20,000 hours (drop to 50% intensity) at 25°C		
Life span in strobe light mode	Est. >50,000 hours (drop to 50% intensity) at 25°C		
Connection	-	JST SMR-03V, 1:+,3:-	JST SMR-03V, 1:+,3:-
Power Supply Selection	-	PSA-24V PSD-24V PSD-STL-48V	PSA-24V PSD-24V PSD-STL-48V