

Coaxial Light

LFV-Si25N


Operating Temperature after 30 minutes	Drawing

Mechanical Data (TYP)	
Casing Material	Aluminum + Diffuser + Mirror
Storage Temperature Range	Temp 0-35°C, Humidity 20-85%
Weight	Approx. 100g

Optical Data (TYP)	R	R24	W	G	B
Illumination (number of LED)	16	16	18		
Led Color	RED		WHITE	GREEN	BLUE
Wavelength	635nm		xy=(0.31,0.32)	525nm	470nm
Led Package	PLCC4		SMD		

Electrical Data (TYP)	R	R24	W	G/B
Operating Voltage	12V ± 2%	24V ± 2%	24V ± 2%	
Reverse Battery Protection	YES		YES	
Supply Ripple Voltage	≤ Vs ± 5%		≤ Vs ± 5%	
Current Consumption	0.08A	0.16A	0.09A	0.06A
Power Consumption	1.92W	1.92W	2.16W	1.44W
Trigger Voltage	Continuous=12V Pulsing 12-24V 0-10% Duty Cycle	Continuous= 24V Pulsing 48V 0-10% Duty Cycle	Continuous= 24V Pulsing 48V 0-10% Duty Cycle	
Operating after 30 minutes	Approx. 41°C		Approx. 41°C	
Additional Cooling Method	Attached to large machine part			
Life span in continuous mode	20,000 hours (drop to 50% intensity) at 25°C			
Life span in strobe light mode	Est. >50,000 hours (drop to 50% intensity) at 25°C			
Connection	JST SMR-02V, 1:+,2:-	JST SMR-03V, 1:+,3:-	JST SMR-03V, 1:+,3:-	
Power Supply Selection	PSA-12V PSD-12V PSD-STL-12V	PSA-24V PSD-24V PSD-STL-48V	PSA-24V PSD-24V PSD-STL-48V	

Application (TYP)	
Recommended Working Distance	5-50mm