

Low Angle Ring Light

LDR-i74LA-UV5


Operating Temperature after 30 minutes	Drawing																																		
<table border="1"> <caption>Operating Temperature Data</caption> <thead> <tr> <th>Minute</th> <th>Temperature (Degree Celsius)</th> </tr> </thead> <tbody> <tr><td>1</td><td>28</td></tr> <tr><td>3</td><td>30</td></tr> <tr><td>5</td><td>32</td></tr> <tr><td>7</td><td>34</td></tr> <tr><td>9</td><td>35</td></tr> <tr><td>11</td><td>36</td></tr> <tr><td>13</td><td>37</td></tr> <tr><td>15</td><td>38</td></tr> <tr><td>17</td><td>39</td></tr> <tr><td>19</td><td>40</td></tr> <tr><td>21</td><td>41</td></tr> <tr><td>23</td><td>42</td></tr> <tr><td>25</td><td>43</td></tr> <tr><td>27</td><td>44</td></tr> <tr><td>29</td><td>44</td></tr> <tr><td>31</td><td>45</td></tr> </tbody> </table>	Minute	Temperature (Degree Celsius)	1	28	3	30	5	32	7	34	9	35	11	36	13	37	15	38	17	39	19	40	21	41	23	42	25	43	27	44	29	44	31	45	
Minute	Temperature (Degree Celsius)																																		
1	28																																		
3	30																																		
5	32																																		
7	34																																		
9	35																																		
11	36																																		
13	37																																		
15	38																																		
17	39																																		
19	40																																		
21	41																																		
23	42																																		
25	43																																		
27	44																																		
29	44																																		
31	45																																		

Mechanical Data (TYP)	
Casing Material	Aluminum
Storage Temperature Range	Temp 0-35°C, Humidity 20-85%
Weight	Approx. 90g

Optical Data (TYP)	UV5
Illumination (number of LED)	60
Led Color	UV
Wavelength	375nm
Led Package	T1 5mm Clear

Electrical Data (TYP)	UV5
Operating Voltage	24V±2%
Reverse Battery Protection	YES
Supply Ripple Voltage	≤ Vs±5%
Current Consumption	0.20A
Power Consumption	4.80W
Trigger Voltage	Continuous= 24V Pulsing 48V 0-10% Duty Cycle
Operating after 30 minutes	45°C
Additional Cooling Method	Attach to large machine part
Life span in continuous mode	5,000 hours (drop to 50% intensity) at 25°C
Life span in strobe light mode	Est. >10,000 hours (drop to 50% intensity) at 25°C
Connection	JST SMR-03V, 1:+, 3:-
Power Supply Selection	PSA-24V PSD-24V PSD-STL-48V

Application (TYP)	
Recommended Working Distance	5-30mm